



POWER STORE.

Model		X8KS-EA-30
Technical Data		
Prime Power	kVA	8
Single Phase Output	V	230
Max Input Charging Current Single Phase	A	60
Peak Power output	kW	8
Energy storage Capacity	kWh	30
Continuous Output	kW	8
Battery Data		
Type		LiFePO4
Quantity	Units	6
Size	V	52
Protection degree	IP	65
Warranty	Years	5
BMS		√
Inverter		
Size	kW	8
Electrical Protection		√
Protection degree	IP	65
Warranty	Years	5
Solar PV Data		
PV Rated Power Input	w	8000
PV Socket	Units	2
Max. Input Current	A	22A/22A
Performance		
Recharge Time	h	3
Max Parallel Connection same model	Units	2
Max Parallel Connection same model output	KVA	16
Max Hybrid Connection input	KVA	6
EMS		√
Earthing		√



POWER STORE.

Connections		X8KS-EA-30
PV Socket	Units	2
RCD Protected Outputs	Units	2
RCD Protected Outputs	A	63/125
230 V Charging Socket	Units	1
Protection degree	IP	54
Dimensions & Weight		
Weight	Kg	500
Length	mm	1100
Height	mm	900
Width Front Face	mm	1100
Housing		Metal casing
Protection degree	IP	54
Warranty	Years	5
Features		
Lift Pockets	Units	4
Tie down points	Units	4
Emergency Stop Button		√
IPMS		√
Charging cable		√
Safety		
Fire extinguishing aerosol device		√

Available from **ESS POWER STORE** www.esspowerstore.co.uk
 Contact : Matt Pierce
 Email : info@esspowerstore.co.uk
 Mobile : 07932 - 055858